



# *Strength*

**DURABILITY  
& PERFORMANCE**

Roseburg's AC Plywood Panel is a **light weight, strong and durable** sanded plywood panel produced with a multi-layered western softwood inner core and a Douglas Fir face. Used primarily as a **performance-based panel**, AC meets the same criteria as sanded panels under APA and U.S. National Standards PS 1. The panel has exceptional **strength and stiffness** for a wide range of applications. Combine the natural beauty of real wood and the manufacturing quality of Roseburg and you get one of the finest panels offered on the market today.

### Face Finishing Details

- Finish Sand
- Minor Wood Putty Repair, Occasional Epoxy

Panel Size	Thickness (inches)	Plys
4' x 8'	1/4, 11/32	3
	15/32, 19/32	5
	23/32	5 or 7 as specified (AC)
	23/32	7 only (AA, AB)
	31/32	7 (AC)
	31/32	9 only (AA,AB)

### Stamping

- AC: Back Stamp = APA Stamp

### Banding and Stencil

- AC: Top Cover - Mark Thickness & Grade
- 3 Bands/3 Stickers

### Packaging Details

Thickness (inches)	Pieces Per Unit	#/MSF	#/Unit
1/4	120	725	2,785
11/32	90	950	2,750
15/32	66	1,350	2,850
19/32	53	1,600	2,715
23/32	44	1,900	2,675
31/32	30	2,700	2,850

### Specifications

**Lengths:** 8'

**Widths:** 4'

**Thickness:** 1/4", 11/32", 15/32", 19/32", 23/32", 31/32"

#### Construction Details:

**Face:** Douglas Fir

**Core:** Western Softwood

**Centers:** Western Softwood

**Backs:** Western Softwood

Fully water resistant NAUF phenolic resin

Meets APA PS 1-09 standards

FSC Panels Available